


# PCE-5132

## LGA1200 10th Generation Intel® Core™ i9/ i7/i5/i3/Pentium/Celeron System Host Board with DDR4, SATA 3.0, USB 3.2, M.2, Dual GbE, and Triple Displays



### Features

- Intel® Core™ i9/i7/i5/i3 LGA1200 processor with Q470E chipset
- Up to 64 GB of dual-channel (non-ECC) DDR4 2666/2933 MHz
- PCIe 3.0, M.2, USB 3.2, SATA 3.0, and SW Raid 0, 1, 5, 10
- Supports out-of-band remote management with AMT
- Supports Advantech's LPC modules, SUSI 4.0, and embedded software APIs


Quiet

### Specifications

CE FCC

	CPU	i9-10900K	i9-10900E	i9-10900TE	i7-10700TE	i7-10700E	i5-10500E	i5-10500E	i5-10500TE	i3-10100E	i3-10100TE	G6400E	G5900E	G5900TE	
Processor System	Speed	3.7GHz	2.80GHz	1.80GHz	2.00GHz	2.90GHz	3.10GHz	3.10GHz	2.30GHz	3.60 GHz	2.30GHz	3.80GHz	3.20GHz	3.00GHz	
	L3 Cache	20MB	20MB	20MB	16MB	16MB	12MB	12MB	12MB	6MB	6MB	4MB	2MB	2MB	
	Cores	10	10	10	8	8	6	6	6	4	4	2	2	2	
	TDP	125W	65W	35W	35W	65W	65 W	65W	35W	65W	35W	58W	58W	35W	
	Socket	LGA1200													
	Chipset	Q470E													
	BIOS	AMI 256 Mbit SPI													
Bus	PCI-Express	1 x PCIe x16 and 1 x PCIe x4 to backplane													
	PCI	4 x PCI master to backplane, 32-bit, 33 MHz													
Memory	Technology	Dual-channel (non-ECC) U-DIMM DDR4 2666/2933 MHz (supports x8 DDR4 1024 M)													
	Max. Capacity	up to 64GB (based on CPU)													
	Socket	2 x DDR4 288-pin DIMM													
Graphics	Controller	Chipset integrated with Intel® HD Graphics													
	VRAM	Shared system memory is subject to OS													
	VGA	Supports resolutions of up to 2048 x 1152 @ 60MHz													
	DVI-D	Supports resolutions of up to 1920 x 1200 @ 60MHz													
	Display Port	Supports resolutions of up to 4096 x 2160 @ 60MHz													
	Triple Display	CRT+DP/DVI-D+DP/DVI-D													
Ethernet	Interface	10/100/1000 Mbps													
	Controller	LAN 1: Intel® I219-LM LAN 2: Intel® I210AT													
	Connector with LED	2 x RJ45													
Rear I/O	USB 3.2 (Gen2)	2													
	USB 2.0	1													
	Ethernet	2													
	VGA	1													
Internal Connector	USB	5 x USB 2.0 (1 USB Type A + 4 on backplane)													
	SATA (SW Raid 0,1,5,10)	6													
	M.2 (2280 Type M)	1 (PCIe x4)													
	DP/DVI-D	2 (Pin header)													
	COM	2													
	Parallel	1													
	IrDA	1													
	GPIO	8bit													
Watchdog Timer	Output	System reset													
	Interval	Programmable 1-255 sec													
Miscellaneous	Audio	Intel® High Definition audio interface (requires audio extension module PCA-AUDIO-HDB1E)													
Power Requirement	Test Environment	Intel W-1290E, Memory 2* DDR4 2666U 32GB													
	Voltage	+3.3V, 5V, 12V													
	Current	1.15A, 1.54A, 1.38A													
Environment	Operating											Non-Operating			
	Temperature	0 ~ 60 °C (dependent on CPU and cooler solution)										-40 ~ 85 °C			
	Humidity	40 °C @ 85% relative humidity (non-condensing)										60 °C @ 95% relative humidity (non-condensing)			
Physical	Dimensions (L x H)	338 x 122 mm (13.3" x 4.8")													

## Block Diagram



## Ordering Information

Part Number	PCH	Memory	Backplane	LAN	VGA	DP/DVI-D	COM	SATA III	M.2	USB 2.0	USB3.2 (Gen1)	USB3.2 (Gen2)	S/W Raid	AMT
PCE-5132G2-00A1	Q470E	Non-ECC	PCE-5BXX PCE-7BXX	2	Yes	2*	2	6	1	6	6	2	Yes	Yes

Note: DP/DVI-D cable is optional

## Packing List

Part Number	Description	Quantity
1700003194	Serial ATA HDD data cable	x2
1701260305	COM + printer ports cable kit	x1
2190000902	Warranty card	x1
2041513200	Startup manual	x1

## I/O View



PCE-5132G2-00A1

## Optional Accessories

Part Number	Description
1960049408N001	CPU cooler for 1U Chassis and 84W TDP
1960050255N001	CPU cooler for 2U Chassis and 95W TDP
1960052651N021	CPU cooler for 2U/4U Chassis and 80W TDP
1960067860N001	CPU cooler for 2U/4U chassis and 125W TDP
PCA-AUDIO-HDB1E	Audio module
PCA-COM232-00A1E	4-port RS-232 LPC module
PCA-COM485-00A1E	4-port RS-422/485 LPC module
1700002204	2-port USB2.0 cable w/BKT (27 cm)
1700020277-01	2-port USB 3.0 cable w/ BKT (30 cm)
1700031719-01	4-port USB 3.0 cable w/ BRK (30 cm)
1700021831-01	DP to DVI-D cable w/ BKT
PCE-DP10-00A1E	DP to DP cable w/ BKT
PCA-TPM-00B1E	TPM 2.0 Module
PCE-SA01-00A1E	Extension Stack Board
20706WX9HS0097	PCE-5132 win 10 embedded OS (high-end)
20706WX9VS0101	PCE-5132 win 10 embedded OS (value)
20706WX9ES0111	PCE-5132 win 10 embedded OS (entry)

\* for PCE-7132/5132/5032, PCE-SA01-00A1E miniPCIe only support PCIe1x signal