


W24IB7T-POA2 23.8" Panel PC (Intel® Celeron BayTrail N2930 1.83GHz)


Mechanical Design



Open Frame



Mechanical design




- | | |
|---------------------------|------------------|
| 1. Audio Jack | 7. VGA |
| 2. 1 x RS232 (Optional) | 8. RS232 |
| 3. DVI (Optional)* | 9. PS/2 |
| 4. LAN | 10. 12V DC in |
| 5. USB (1 x 3.0, 3 x 2.0) | 11. Dimming Knob |
| 6. RS232/422/485 | 12. OSD Membrane |

* Only 2 display output at the same time

Fully Integrated I/O

Dimensions



- * Measurements shown in mm
- * Tolerance of all dimensions is shown as follow 0~30 mm ± 0.1 mm,
- * 30~50 mm ± 0.15 mm, 50~120 mm ± 0.2 mm, above 120 mm ± 0.25 mm
- * Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

Specifications

System :

- CPU : Intel® Celeron® Bay Trail-M N2930 1.83GHz
- System Chipset : Intel® Atom SoC Integrated
- Memory Slot : SODIMM DDR3L 1600 Max. 8GB
- IDE/SATA : 1 x SATA II
- LAN : Intel® I210-AT GbE LAN x 2
- Audio Codec : Realtek HD Audio Codec

Panel Spec :

- Size/Type : 23.8" TFT
- Resolutions : 1920 x 1080
- Brightness : 250 cd/m² (typ.)
- Contrast Ratio : 3000 : 1 (typ.)
- Viewing Angle : -89~89(H); -89~89(V)
- Max. Colors : 16.7M (8 bits/colors)

Input / Output :

- Serial Ports : 2 x RS232, 1 x RS232/422/485
 - USB Ports : 1 x USB 3.0, 3 x USB 2.0
 - Keyboard / Mouse : 2 x PS/2
 - Ethernet : 2 x RJ 45-10/100/1000 Mbps
 - VGA : 1 x VGA (female)
 - Audio : Line-Out, Line-In, Mic in
- Default setting: RS232

Environment Considerations :

- Operating Temperature : 0 °C to 50 °C
- Operating Humidity : 30% to 90% (non condensing)

OS BSP / Driver Support :

- Support Windows 10 IoT Enterprise / Windows 8 embedded / Windows 7 embedded

Security Support

- Trusted Platform Module (TPM 1.2)

Expansion Slot :

- 2 x Mini PCIe (1 for WiFi, 1 for WWAN Module)

Power Specifications :

- Power Input : 12V DC IN (Lockable Power Jack)
- Power Consumption : 100W (typ.)(Max.backlight & high CPU load)

Accessories :

- External Adapter : 110~240V Ac-in Power Adapter

Order Options :

Mechanical : Open Frame	Storage : 2.5" HDD/2.5" SSD/mSATA SSD
Touch : P-CAP	RAM : SODIMM DDR3L 1600 Max.8GB
	OS : Windows 10 IoT Enterprise Windows 8 embedded / Windows 7 embedded (Optional)

