

iROBO-MC420N-NS3-AC

42" Galvanized steel Wall Mount Display



Features

- 42" TFT-LCD 16:9 Panel PC
- Full HD Resolution
- High Brightness optional available
- 3 Years Warranty

Specifications

Display

- LED Size: 42" 16:9
- Resolution: 1920 x 1080
- Brightness: 350 cd/m² (optional 700 cd/m²)
- Contrast Ratio: 3000:1
- Viewing Angle (H/V°): 178 / 178
- Display Area: 931 x 524 mm
- Screen Diagonal: 1067,3 mm
- Display Surface: 3H, Anti-glare
- Backlight: LED
- Backlight MTBF (hrs): 30000
- Response Time: 6.5 ms

Touch Screen

- no
- Optional: Infrared, Support 10 Points, USB interface IK07, Hardness of touch glass 7H

OSD Function

- OSD keys on rear side

Audio

- Line in 3.5 mm jack, 2x 10W Speakers in Front Frame

Rear I/O

- 1x VGA
- 2x HDMI 1,4
- 1x USB Touch
- 1x USB for Media Stick
- Supported playback format: mp3, m4a, Jpg, bmp, png, avi, mpg, dat, vob, mov, mkv, rm, rmvb, mp4, mjpeg, ts, trp, wmv, asf, flv
- Power input DC Power Jack, (Optional terminal block)
- 1x Audio Line-in

Power Supply

- Power input: 100~240V AC with C14 Female Socket

Mechanical

- Galvanized Steel (SECC)
- IP front protection: no
- Mounting: Wall mount VESA 300x300

Dimensions

- Dimension (W x H x D mm): 1047 x 602 x 77 mm
- Weight: 30 kg Net / 36 kg Gross

System & Environment

- Operating temperature: 0°C to 50°C
- Storage temperature: -20°C to 60°C

Certifications

- CE

Optional Features

- Wall-mount

Package Contents:

- 1x HDMI Cable Male to Male 1.5M
- 1x USB Touch Cable 1.5M
- 1x EU AC Power Cable 1.8M

Dimension



Ordering Information

- iROBO-MC420N-NS3-AC
42" Industrial Display, Non-Touch, 1920x1080, 16:9, 350cd/m2,
Non-Touch, VGA, DVI, 2xHDMI, Audio, 100~240V AC-In