



WADE-2232Q

Rugged and Stylish Industrial Mini-ITX Barebones Chassis with 220W Active PFC PSU



The WADE-2232Q is a rugged and stylish barebones chassis suitable for embedded applications that stand alone or are rackmounted. Its effective ventilation is achieved by the mesh design of the front panel. No actual tool is needed to release

the top cover of chassis, simplifying integration and field service. This barebones chassis can be installed with a WADE series board, 220-watt power supply, 3.5" drive bay and two PCI expansion slot.

FEATURES

- Barebones Chassis for Mini-ITX board
- Tool-free mechanism to open the top cover
- Rugged and stylish design
- Quick 3.5" HDD installation by releasing the top cover
- Two PCI slots supported

REAR I/O



POWER SUPPLY	FSP220-60LE optional
Input Voltage	90V ~ 264V AC, full range
Input Frequency	47 ~ 63 Hz
Input Current	5A@115V, 3A@230V
Efficiency	>80%
Holdup Time	17ms. at full load@25°C
Over Voltage Protection	+5V@5.5~6.8V; +3.3@3.5~4.8V; +12V@13.4~15.6V
Over Power/Load Protection	Output power over to 110%~140%
MTBF	100,000 hrs
EMI & Safety Approval	UL, TUV, CE, FCC, CB, CSA, SEMKO, FIMKO, NEMCO, DIMCO
Temperature/Humidity	Operating: -10 ~ 50°C, 20 ~ 85%RH Storage: -40 ~ 70°C, 10m ~ 90%RH
Dimension (WxDxH)	150x81.6x40.6 mm; 5.9"x3.2"x1.6"

ORDERING GUIDE

- **WADE-2232Q-582R-220X**
Rugged and stylish industrial Mini-ITX Bare-bones Chassis with 220W active PFC PSU (Core™ 2 Quad Solution)

MECHANICAL & ENVIRONMENTAL	
Operation Temperature	0~50°C
Storage Temperature	-20~80°C
Relative Humidity	5~95% non-condensing
Dimension	310 x 253 x 109 (mm)
Weight	3.5 Kg