

IPC962-511-FL


2-slot Fanless Barebone System with 7th/6th Gen Intel® Core™ i7/i5/i3 & Celeron® Processor (up to 3.4 GHz), Intel® H110 Chipset, PCIe and PCI Slots

Features

- 7th/6th gen Intel® Core™ i7/i5/i3 & Celeron® processor, up to 35 W (codename: Skylake/Kaby Lake)
- Intel® H110 chipset
- Supports 2 expansion slots
- Supports power input: 24VDC (uMin=19V/uMax=30V)
- Compact & front I/O design
- -10°C to +60°C wide operating temperature range with W.T. SSD
- Supports Intel® AMT 9.0
- Supports 2 hot-swappable 2.5" HDD
- Supports optional WLAN module & antenna



▲ Rear view



1. Antenna x 2
2. Remote switch
3. MIC-in x 1/Line-out x 1
4. Ethernet x 2
5. VGA
6. Reset
7. Power switch
8. Terminal block
9. HDD/Power LED
10. USB 3.0 x 4
11. HDMI
12. (1) AX93511: 4 x RS-232/422/485 module (default RS-232)
(2) AX93512: 2 x RS-232/422/485 w/ isolated 2.5KVDC protection & 4-in/4-out isolated DIO
(3) AX93513: 8-in/8-out isolated DIO with interrupt
13. (1) AX96205: 1 PCIe x16 + 1 PCIe x4
(2) AX96206: 1 PCIe x16 + 1 PCI
(3) AX96207: 2 PCI

Specifications

Standard Color	Silver	
Construction	Aluminum extrusion heavy-duty cold-rolled steel, IP40 (w/o fan module)	
Processor System	CPU Level	7th/6th gen Intel® Core™ i7/i5/i3 & Celeron® processor up to 35W (codename: Skylake/Kaby Lake)
	Max. Speed	3.4 GHz
	Chipset	Intel® H110
	System Memory	2 x DDR4-2133 un-buffered SO-DIMM max. up to 32GB
System I/O	1 x Switch for power on/off (ATX) 1 x Remote switch 1 x Power LED 1 x HDD LED 1 x 3-pin terminal block 1 x AT/ATX selectable switch 2 x 10/100/1000 Mbps Ethernet (Intel® i211AT) 4 x USB 3.0 1 x HDMI 1 x VGA 1 x Mic-in 1 x Line-out	
Extension System IO Module	AX93511: 4 x RS-232/422/485 module (default RS-232) AX93512: 2 x RS-232/422/485 w/ isolated 2.5KVDC protection & 4-in/4-out isolated DIO AX93513: 8-in/8-out isolated DIO with interrupt	

Expansion Interface	AX96205: 1 PCIe x16 + 1 PCIe x4 AX96206: 1 PCIe x16 + 1 PCI AX96207: 2 PCI 1 x full-size PCI Express Mini Card slot with USB interface
Storage	2 x hot-swappable 2.5" HDD (supports 7"/9.5"/15" mm)
System Indicators	1 x power on/off, 1 x HDD
Power Supply	Type: ATX/AT Input: 24VDC (uMin=19V/uMax=30V)
Operation Temperature	1. -10°C ~ +60°C (+14°F ~ +140°F) with 6th gen Intel® Core™ and W.T. HDD or W.T. SSD 2. -10°C ~ +55°C (+14°F ~ +140°F) with 7th gen Intel® Core™ and W.T. HDD or W.T. SSD (TBC)
Storage Temperature	-20°C ~ +80°C (-4°F ~ +176°F)
Humidity	10% ~ 90%, non-condensing
Dimensions	147.5 mm (5.80") (W) x 192 mm (7.54") (H) x 230 mm (9.04") (D)
Weight (net/gross)	4.382 kg (9.66 lb)/5.346 kg (11.80 lb)
Certification	CE compliance

* All specifications and photos are subject to change without notice.

Ordering Information

System

IPC962-511-FL-DC	2-slot fanless embedded system with 7th/6th gen Intel® Core™ i7/i5/i3 processor and Intel® H110
------------------	---

Optional

2.5" SATA HDD/SSD	
DDR4-2133 un-buffered SO-DIMM max. up to 32GB	
8816G9620A0E	IPC962-511-FL fan module kit
8816G9621A0E	Wall mount bracket kit
50906D24000E	Adaptor 24V/120W, wire only
	AX92320: 4-port PCI Express GbE PoE communication card
	AX93511: 4 x RS-232/422/485 IO module (default RS-232)
	AX93512: 2 x RS-232/422/485 w/ isolated 2.5KVDC protection & 4-in/4-out isolated DIO module
	AX93513: 8-in/8-out isolated DIO module with interrupt
	AX96205: 1 x PCIe x16 + 1 PCIe x4 expansion kit
	AX96206: 1 x PCIe x16 + 1 PCI expansion kit
	AX96207: 2 x PCI expansion kit

Power Protection

DC Version

OVP (over voltage protection)
SCP (short circuit protection)
OCP (over current protection)

Packing List

- 1 x IPC962-511-FL unit
- 1 x Driver CD
- 1 x Screw pack
- 4 x Foot pad
- 1 x CPU grease
- 1 x Terminal block
- 1 x Remote power switch cable
- 1 x Holder bracket

Dimensions

