



BMX-T522-SK

Intel® 6th Gen Core™ SoC i7/i5/i3 & Celeron® BGA Processor Mini ITX Fanless Box PC



- > DP++, HDM/DP, Dual Display
- > 2 x Intel® I211-AT Gigabit Ethernet
- > 2 x 260-pin DDR4 2133 MHz SO-DIMM Socket, Supports up to 32GB Max (Default: 1 x 4GB DDR4 Memory)
- > 4 x USB 2.0, 4 x USB 3.0, 1 x Mic-In, 1 x Line-Out
- > 4 x RS-232, 2 x RS-232/422/485, 16-bit GPIO by 2 x DB9
- > 2 x 2.5" Internal Bracket, 1 x SD Card Slot, 1 x SIM Card Slot
- > 1 x M.2 Type B 3042/2242/2260/2280 w/ SIM card slot, 1 x M.2 Type A
- > Onboard Infineon SLB9665 TPM 2.0
- > DC in +12V (Lockable DC Jack)

+ Spec

System Information	
Processor	Intel® 6th Gen Core™ SoC i7/i5/i3 & Celeron® BGA Processor
System Memory	2 x 260-pin DDR4 2133 MHz SO-DIMM Socket, Supports up to 32GB Max (Default: 1 x 4GB DDR4)
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
SBC	EMX-SKLUP
Expansion	
Expansion	1 x M.2 Key B 3042/2242/2260/2280 w/ SIM card slot 1 x M.2 Key A 2230 Supports WiFi Module
Storage	
Storage	1 x SD card slot support SD/ SDHC Card 2 x 2.5" Internal HDD Bracket
I/O	
USB Port	4 x USB 3.0, 4 x USB 2.0
COM Port	4 x RS-232 (pin9 with power) 2 x RS-232/422/485
GPIO	2 x 8-bit GPIO by DB9 connector
SIM Slot	1 x SIM Card Slot
Other	2 x SMA Connector (Optional)
Display	
Graphic Chipset	Intel® 6th Gen Core™ SoC i7/i5/i3 & Celeron® BGA Processor
Spec. & Resolution	HDMI: 3840 x 2160 @ 30 Hz, 2560 x 1600 @ 30 Hz DP: 4096x2160 @ 60Hz DP: 4096x2160 @ 60Hz DP + DP, DP + HDMI
Multiple Display	Dual Display
Audio	
Audio Codec	Realtek ALC888S Audio Codec
Audio Interface	Mic-In and Line-Out
Ethernet	
LAN Chipset	1 x Intel® i211AT & 1 x Intel® i219LM Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ45
Power Requirement	
DC Input	DC in +12V~24V
DC Input Connector	DC Jack (lockable)
Power Mode	ATX
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A)
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F) (w/HDD), ambient w/ air flow 0°C ~ 55°C (32°F ~ 131°F) (w/Wide-temp. SSD, M.2), ambient w/ air flow
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	180 x 182 x 76 mm
Weight	3.5kg
Construction	Aluminum + Metal
Ordering Information	



Ordering Information

BMX-T522-SKC-B1R (CPU: 3955U)
BMX-T522-SK3-B1R (CPU: i3-6100U)
BMX-T522-SK5-B1R (CPU: i5-6300U)
BMX-T522-SK7-B1R (CPU: i7-6600U)
Intel® 6th Gen Core™ SoC i7/i5/i3 & Celeron® BGA Processor Mini ITX Fanless Box PC
E1961361013R / 44 x 46.8 x 8.8 Din Rail kit