



## OFT-21WR1

### 21.5" Open Frame Tablet with RK3288

- > RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
- > 2GB RAM
- > 16GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > M.2 B-Key(3042) connector socket
- > 802.11 b/g/n Wireless LAN and Bluetooth 4.0
- > DC 12~24V Input
- > G sensor
- > OS Image support Android 8.1

#### + Spec

##### System Information

<b>Processor</b>	RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
<b>System Memory</b>	2GB DDR3L RAM

##### Storage

<b>Storage</b>	16GB eMMC
----------------	-----------

##### Panel

<b>LCD Size</b>	21.5
<b>LCD Panel</b>	TFT-LCD
<b>Resolution</b>	1920x1080
<b>Pixel pitch</b>	0.24795 X 0.24795 mm
<b>Luminance</b>	250 cd/m2(typ)
<b>Contrast ratio</b>	3000
<b>Viewing angle</b>	178 (H), 178 (V)
<b>Response time</b>	30 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	Projective Capacitive
<b>Touch Light Transmission</b>	85%

##### I/O

<b>External I/O Connector</b>	1 x Power Jack 1 x HDMI Port 2 x USB Type A Host 1 x RJ45 1 x Headphone Jack 1 x Reset
<b>Internal I/O Connector</b>	1 x Micro USB 1 x USB interface , 1 x DMIC interface 1 x USB touch interface 1 x M.2 B-Key(3042) 1 x touch button control(power/vol/brightness) 1 x Power interface (12~24V) 1 x JLVDS1 1 x eDP 1 x AMIC interface 1 x Speaker interface 1 x JSEN1 interface (I2C x2) 1 x JITP1 interface 1 x Debug port 1 x RS232 interface 1 x RS232 , RS485 1 x JGPIO1 (GPIO 16bit) 1 x RTC Battery interface 1 x Micro SIM Card socket for LTE module 1 x Micro SD slot

##### Wireless Communication

<b>WLAN</b>	802.11 b/g/n
-------------	--------------

##### Display

<b>Multiple Display</b>	LVDS+HDMI
-------------------------	-----------

##### Certifications

<b>Certification Information</b>	CE, FCC Class A
----------------------------------	-----------------

##### Mechanical & Environmental



<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	501.88 x 294.2 x 44.1mm
<b>Weight</b>	3.4kg
<b>Power Requirement</b>	DC 12~24V Input
<b>Power Mode</b>	DC Jack, DC input 4pin header
<b>Software Support</b>	
<b>OS Information</b>	Android 8.1
<b>Ordering Information</b>	
<b>Ordering Information</b>	OFT-21WR1-2G_16G-Android 8.1-DC in