


# PCE-5029

## Intel® Core™ i LGA1151 System Host Board with DDR4, SATA 3.0, USB 3.0, Dual GbE, and Dual Displays

**NEW**



### Features

- Intel® Core™ i7/i5/i3 LGA1151 processor with H110 chipset
- Up to 32 GB of dual-channel (non-ECC) DDR4 1866/2133 MHz
- PCIe 3.0, USB 3.0, and SATA 3.0 slots
- Supports CRT and DVI-D/DP display (with optional cable)
- Supports Advantech's LPC modules, SUSIAccess, and embedded software APIs

CE FCC

### Specifications

Processor System	CPU	i7-6700	i7-6700TE	i5-6500	i5-6500TE	i3-6100	i3-6100TE	G4400	G4400TE	G3900	G3900TE		
	Speed	3.4 GHz	2.4 GHz	3.2 GHz	2.3 GHz	3.7 GHz	2.7 GHz	3.3 GHz	2.9 GHz	2.8 GHz	2.6 GHz		
	Cache	8 MB	8 MB	6 MB	6 MB	4 MB	4 MB	3 MB	3 MB	2 MB	2 MB		
	SKU/Chipset	Intel® H110											
	BIOS	AMI® SPI Flash 128 Mbit											
Bus	PCI-Express	1 x PCIe x16 and 1 x PCIe x4 to backplane											
	PCI	4 x PCI master to backplane, 32-bit, 33 MHz											
Memory	Technology	Dual-channel (non-ECC) U-DIMM DDR4 1866/2133 MHz											
	Max. Capacity	32 GB (16 GB per DIMM)											
	Socket	2 x DDR4 288-pin DIMM											
Graphics	Controller	Chipset integrated with Intel® HD Graphics											
	VRAM	Shared system memory is subject to OS											
	CRT	Supports resolutions of up to 1920 x 1200 pixel @ 60 MHz											
	DVI-D	Supports resolutions of up to 1920 x 1200 pixel @ 60 MHz											
	Display Port	Supports resolutions of up to 1920 x 1080 pixel @ 60 Hz											
	Dual Display	CRT+DP/CRT+DVI											
Ethernet	Interface	10/100/1000 Mbps											
	Controller	LAN 1: Intel® I219-V LAN 2: Intel® I211-AT											
	Connector with LED	RJ45 x 2											
Rear I/O	USB 3.0	1 (G2 SKU)											
	Ethernet	1 (VG SKU); 2 (G2 SKU)											
	VGA	1											
	Serial	1 (VG SKU)											
	PS/2	1 (PS/2 Y cable supports 1 x keyboard and 1 x mouse)											
Internal Connector	USB	7 x USB 2.0 (pin header*2 + USB Type A*1 + 4 on backplane) 2 x USB 3.0 (pin header)											
	SATA	4											
	DP/DVI-D	1 (Pin header)											
	COM	2 (G2 SKU) 1 (VG SKU)											
	Parallel	1											
	GPIO	8 bits											
Watchdog Timer	Output	System reset											
	Interval	Programmable 1-255 sec											
Miscellaneous	Audio	Intel® High Definition audio interface (requires audio extension module PCA-AUDIO-HDB1E)											
Power Requirement	Test Environment	i7-6700, 3.4 GHz, 65 W, with 2 x 8-GB DDR4 2133											
	Voltage	+12V	+5V	+3.3V	+5Vsb								
	Current	2.64A	1.23A	0.19A	0.09A								
Environment	Operating Temperature	0 ~ 60 °C (dependent on CPU and cooler solution)								Non-operating			
	Humidity	40 °C @ 85% relative humidity (non-condensing)								-40 ~ 85 °C			
										60 °C @ 95% relative humidity (non-condensing)			
Physical	Dimensions (L x W)	338 x 122 mm (13.3 x 4.8")											


ADVANTECH

Slot SBC & Passive Backplanes

All product specifications are subject to change without notice.

Last updated: 5-May-2016

## Block Diagram



## Ordering Information

Part Number	Chipset	Memory	Backplane	Display	USB 3.0	USB 2.0	COM	GbE LAN	AMT	SATA	SW RAID	Intelligent System Module Support
PCE-5029G2-00A1E	H110	Non-ECC	PCE-5BXX	VGA + DVI/DP*	3	7	2	2	No	4	No	Yes
PCE-5029VG-00A1E	H110	Non-ECC	PCE-5BXX	VGA	2	7	2	1	No	4	No	No

\*Note: DP cable (P/N: PCE-DP10-00A1E) and DVI-D

## Packing List

Part Number	Description	Quantity
1700003194	Serial ATA HDD data cable	x2
1700022749-11	Serial ATA HDD power cable	x1
1701260305	COM + printer ports cable kit	x1
1700060202	Keyboard and mouse Y-cable	x1
1700002204	2-port USB cable kit	x1
9689000068	Jumper package	x1
2190000902	Warranty card	x1
2001512910	Startup manual	x1
2061512900	Utility CD	x1

## Optional Accessories

Part Number	Description
1700020277-01	2-port USB 3.0 cable w/ BKT (30 cm)
1700002204	2-port USB 2.0 cable w/ BKT (27 cm)
1700021831-01	DP to DVI-D cable w/ BKT for G2 SKU
1701090401	Single COM cable (40 cm)
1701092300	Dual COM cable (28.5 cm)
1960052651N021	CPU cooler for 2U, 4U, and wallmount chassis
1960049408N001	CPU cooler for 1U chassis
PCA-TPM-00A1E	TPM module
PCA-COM485-00A1E	4-port RS-422/485 LPC module
PCA-COM232-00A1E	4-port RS-232 LPC module
PCE-DP10-00A1E	DP redriver board (25 cm) for G2 SKU
PCA-AUDIO-HDB1E	Extension module for HD audio

## I/O View



PCE-5029G2-00A1E



PCE-5029VG-00A1E